



Loncin

Generator
Model: **LC3800DC**



- Durable, Professional Generator
- High performance rating
- Sturdy Roll-over frame
- Dual Voltage system
- Electric start and wheel kits optional
- Low noise level
- Fuel efficient for 13 hrs autonomous running
- Supplied with 16A, 230 / 110V, Industrial U.K. standard sockets.



Generator

Model: **LC3800DC**

SPECIFICATION:

ENGINE	single cylinder, Forced Air cooled, 4 stroke	
	Rated Power (KW/3000rpm)	5.1
	Starting System	Recoil Start
	Ignition system	T.C.I.
	Displacement (cc)	242
	Fuel Consumption (L/ hr)	1.9
	Fuel Tank Capacity	25
	Oil Capacity (L)	1.1
	Noise level	69 (at 7m)
	Continuing operating hours (h)	13
GENERATOR	Charging Voltage V	12 (DC)
	Charging Current A	8.3
	Rated Frequency (HZ)	50/60
	Rated Voltage (V)	110/220/230/240
	Rated Power (KW)	2.8
	Max. Power (KW)	3.1
DIMENSIONS	L(mm)×W(mm)×H(mm) – (electric start)	680 (855)×540×550
	Dry Weight (kg)	72
ACCESSORIES	Large-size air cleaner	○
	Large-size muffler	○
	Large-size fuel tank	○
	Fuel Gauge	○
	Voltmeter	○
	Automatic voltage regulator	○
	Oil alarming system	○
	Non-fuse breaker	○
	Battery holder	Optional (in case electric start)